



Hveem Stabilometer - ASTM Type

Code: 45-7500

Product Group: Hveem Stabilometer

ASTM Type. Includes displacement dial indicator, diaphragm tester with polyurethane dummy specimen, two followers, rubber bulb, extra O-rings, 1 qt. of oil, wrench, assembly tool and instructions.

Standards

ASTM D1560, ASTM D2844, AASHTO T190, AASHTO T246

Specification

Specimen Size	4" (101.6 mm) diam.
Gauge	200 psi capacity; 1/4% accuracy.
Loading	Diaphragm/piston pump.
Shell	Aluminum-Magnesium; adjustable stage.
Pressure Fluid	1 qt. hydraulic fluid (included).
Dial Indicator	1.0" displacement x 0.001" divisions.
Followers	Two included; one 3.985" $\pm$ 0.005" diam. x 5-1/2"; one 3.95" $\pm$ 0.005" diam. x 5" h.
Weight	Net 55 lbs. (24.9 kg).

Accessories



Dial Indicator - 1.0" Range

Code: 88-4100



Hveem Diaphragm Replacement Tool

Code: [45-7520](#)



R-Value Rough Hveem Test Mold

Code: [45-7505/10](#)



S-Value Smooth Hveem Test Mold

Code: [45-7505/12](#)

Spares/Consumables



Diaphragms


Code: [45-7500/12](#)



Hveem Test Block


Code: [45-7500/10](#)

Alternatives



Hveem Stabilometer - California Type

Code: [45-7505](#)



Hveem Stabilometer - Texas Type

Code: [45-7510](#)