



Mechanical Analysis Stirrer 120vAC

Code: 24-4132/02

Product Group: Mechanical Analysis Stirrer

Standards

ASTM D422, AASHTO T88

Further Information

110vAC, 50/60 Hz, 1ø. 125 Watts

Specification

Motor	Universal AC-DC; up to 75 cycles; 3-speed selectable.
Speeds at No Load	Low: 13 ,000 rpm. Medium: 16,000 rpm. High: 18,000 rpm.
Housing	Die-cast aluminum; stainless steel front panel; baked enamel finish.
Controls	Rotary speed control switch; on-off switch.
Mixing Paddle	Disc-shaped; nickel-plated steel.
Dispersion Cup	4 stationary baffles, permanently mounted; rounded bottom.
Dimensions	7" w. x 6-1/2" d. x 20" h. (178 x 165 x 508 mm).
Weight	Net 15 lbs. (7 kg).
Motor	Universal AC-DC; up to 75 cycles; 3-speed selectable.
Speeds at No Load	Low: 13 ,000 rpm. Medium: 16,000 rpm. High: 18,000 rpm.
Housing	Die-cast aluminum; stainless steel front panel; baked enamel finish.
Controls	Rotary speed control switch; on-off switch.
Mixing Paddle	Disc-shaped; nickel-plated steel.

Dispersion Cup	4 stationary baffles, permanently mounted; rounded bottom.
Dimensions	7" w. x 6-1/2" d. x 20" h. (178 x 165 x 508 mm).
Weight	Net 15 lbs. (7 kg).

Spares/Consumables



Mixing Paddle

Code: [24-4132/11](#)



Soil Dispersion Cup

Code: [24-4132/10](#)

Alternatives



Mechanical Analysis Stirrer 220-240vAC

Code: [24-4132/01](#)