



Mechanical Dial Indicator - 10 mm Range

Code: [88-4080](#)

Product Group: [Mechanical Dial Indicators](#),
[Pneumatic Consolidation Apparatus](#), [Table Top Consolidation Apparatus](#)

Specification

Range	10 mm
Divisions	0.0025 mm
Movement	Counter-clockwise
Face Diameter	92 mm
Contact Point	Immediate response, up or down; tip movement magnified to indicator hand with minimal friction; 3/16" (5 mm) radius x 1/4" (6 mm) l.
Dials	With continuous graduations and revolution counters.
Measure Movement	Measure movement away from dial case; pointer at zero with stem retracted.
Weight	Net 12 oz. (340 g).

Accessories

1" Extension Point

Code: [88-4154](#)



1/2" Extension Point

Code: [88-4152](#)





1/4" Extension Point

Code: [88-4150](#)



3" Extension Point

Code: [88-4156](#)



Electronic Digital Indicator, 0.600"/15 mm range

Code: [88-4210](#)



Mechanical Dial Indicator - 0.4" Range

Code: [88-4070](#)



Mechanical Dial Indicator - 1.0" Range Counter Clockwise Movement

Code: [88-4120](#)



Mechanical Dial Indicator - 25 mm Range Counter Clockwise Movement

Code: [88-4130](#)

Alternatives



1" Extension Point

Code: [88-4154](#)



1/2" Extension Point

Code: [88-4152](#)



1/4" Extension Point

Code: [88-4150](#)



3" Extension Point

Code: [88-4156](#)



Electronic Digital Indicator, 0.600"/15 mm range

Code: [88-4210](#)



Mechanical Dial Indicator - 0.4" Range

Code: [88-4070](#)



Mechanical Dial Indicator - 1.0" Range Counter Clockwise Movement

Code: [88-4120](#)



Mechanical Dial Indicator - 25 mm Range Counter Clockwise Movement

Code: [88-4130](#)