



## Mechanical Dial Indicator - 25 mm Range Counter Clockwise Movement

Code: 88-4130

Product Group: Mechanical Dial Indicators,  
Pneumatic Consolidation Apparatus, Table Top  
Consolidation Apparatus

### Specification

Range	25 mm
Divisions	0.1 mm
Movement	Counter-clockwise
Face Diameter	57 mm
Contact Point	Immediate response, up or down; tip movement magnified to indicator hand with minimal friction; $3/16"$ (5 mm) radius x $1/4"$ (6 mm) l.
Dials	With continuous graduations and revolution counters.
Measure Movement	Measure movement away from dial case; pointer at zero with stem retracted.
Weight	Net 12 oz. (340 g).

### Accessories

#### 1" Extension Point

Code: 88-4154



#### 1/2" Extension Point

Code: 88-4152





## 1/4" Extension Point

Code: [88-4150](#)



## 3" Extension Point

Code: [88-4156](#)



## Electronic Digital Indicator, 0.600"/15 mm range

Code: [88-4210](#)



## Mechanical Dial Indicator - 0.4" Range

Code: [88-4070](#)



## Mechanical Dial Indicator - 1.0" Range Counter Clockwise Movement

Code: [88-4120](#)



## Mechanical Dial Indicator - 10 mm Range

Code: [88-4080](#)

---

### Alternatives



#### 1" Extension Point

Code: [88-4154](#)



#### 1/2" Extension Point

Code: [88-4152](#)



#### 1/4" Extension Point

Code: [88-4150](#)



#### 3" Extension Point

Code: [88-4156](#)



## Electronic Digital Indicator, 0.600"/15 mm range

Code: [88-4210](#)




## Mechanical Dial Indicator - 0.4" Range

Code: [88-4070](#)



## Mechanical Dial Indicator - 1.0" Range Counter Clockwise Movement

Code: [88-4120](#)



## Mechanical Dial Indicator - 10 mm Range

Code: [88-4080](#)