



Unconfined Compression Tester, Hand-Operated

Code: [25-3605](#)

Product Group: [Unconfined Compression Tester,
Hand-Operated](#)

6.6 kN load capacity.

Standards

ASTM D2166, AASHTO T208

Specification

Specimen Height	Up to 8" (203 mm).
Platens	3" (76 mm) diam.; with concentric grooves for centering specimen.
Proving Ring	Plated steel; complete with dial indicator and calibration charts in English and Metric units.
Strain Indicator	English: 1.0" range x 0.001" graduations. Metric: 25 mm range x 0.01 mm graduations.
Hand Crank	Two-piece; aluminum.
Base	One-piece; cast aluminum.
Crosshead	High-strength aluminum.
Dimensions	10-5/8" w. x 6-3/8" d. x 26-1/4" h. (270 x 162 x 667 mm).
Weight	Net 43 lbs. (19.5 kg); Shpg. 58 lbs. (26.3 kg).

Accessories



Unconfined Compression Test Accessory Set, English

Code: [25-3997](#)



Unconfined Compression Test Accessory Set, Metric

Code: [25-3998](#)

Alternatives



Unconfined Compression Tester, Hand-Operated

Code: [25-3602](#)



Unconfined Compression Tester, Hand-Operated

Code: [25-3604](#)



Versa-Loader

Code: 25-3525/02